

PS32

THE PRACTICAL POS FOR **MODERN RETAIL — BUILT FOR** SPEED, SIZE, AND SIMPLICITY.







Restaurant

Specifications

MAIN MONITOR PERFORMANCE

Processor

CPU Hexa core (A78+A55) GPH Mali-G57 MC2

Operating system

Android 13

Memory

RAM/Flash 4 GB / 32 GB

I/O and I/F

USB 2 x USB A 3.0

2 x USB A 2.0 1 x USB C 2.0

1 x USB C (3.0/DP 1.4), multi function

1 x DC 24 V / 2.5 A input Power

1 x Type-C Port Video 1 x 3.5 mm Mic in Audio 1 x 3.5 mm Line out

2 x RS232 (RJ50) Communication

1 x Ethernet

1 x R.J12 Cash drawer **Buttons** 1 x power

DISPLAY

15.6" FHD with touch, 350nits, 50,000h

NETWORK

Ethernet 10/100/1000 Mbps supported

USER ENVIRONMENT

0°C to 50°C Operating 32 °F to 122 °F temperature

-20 °C to 60 °C Storage temperature -4 °F to 140 °F

Storage 10% to 80% humidity

Electrostatic ±8K contact discharge

±15K air discharge

SECOND MONITOR PERFORMANCE

Display Specification

15.6" FHD with touch, 350nits, Main Display

50,000h

15.6" FHD with touch, 350nits, 2nd. Display

50.000h 15.6" FHD without touch, 350nits,

50.000h

10.1" HD without touch, 350nits,

50,000h

Housing PC+ABS

Main Monitor: 3W speaker Speaker

Second Monitor: NA

100 x 100 Vesa hole

75 x 75

1 x USB Type-C AD, power, integrated (for DP, Touch Power)

Buttons NA

board I/F

The Android version may vary based on the mobile processor product roadmap. The upgradeable version is subject to change on the manufacturer's policy and















Corporate Headquarters

Point Mobile Co., Ltd. https://www.pointmobile.com/en/contactus +82 2 3397 7870

North America

Point Mobile Americas LLC info@pointmobileamericas.com +1 202 798 0786

Europe Point Mobile Europe GmbH info.pmeg@pointmobile.com +49 211 1588 5913

Point Mobile China info@pointmobile-cn.com +86 755 8869 1169